

ND

NASTRO CURVO DOPPIO FISSO CON SEPARATORE A PALETTE

DOUBLE CURVED FIXED BELT

TAPIS DOUBLE INCLINAISON

FIXE CINTA DOBLE

GEBOGENES FESTES DOPPELBAND


Nastro da affiancare alla pressa. Monta di serie il separatore a palette.

This belt is to be placed next to the press. A blade separator is assembled as standard equipment.


Tapis à double inclinaison à placer à côté de la presse.

Cinta transportadora para colocar debajo de las prensas para plástico. Para la extracción de las piezas ya estampados.

Band zur Anwendung mit der Presse. Es wird serienmäßig ein Palettenabscheider.




Sovrasponde laterali
Lateral extra side wall




Mod.	L	U	I	H min	H max
ND1	1300	250	305	700	1000
ND2	1300	350	405	700	1000
ND3	1300	450	505	700	1000
ND4	1800	250	305	1000	1300
ND5	1800	350	405	1000	1300
ND6	1800	450	505	1000	1300

Quote riferite con inclinazione a 35°
Reported dimensions with 35° inclination
Dimensions rapportées avec inclinaison 35°
Dimensiones referidas con inclinación cinta de 35°
Berichtete Dimensionen mit Neigung 35°




Posizione del nastro parallelo alla pressa.
Parallel position of the conveyor respect the moulding machine.

Tapis posé latéralement à la presse.
Posición de la cinta en paralelo a la máquina.
Seitlich der Spritzgussmaschine aufgestelltes Förderband.



Posizione del nastro interno alla pressa.
Conveyor inside of the moulding machine.

Tapis posé à l'intérieur de la presse.
Posición de la cinta dentro de la máquina.
In die Spritzgussmaschine integriertes Förderband.



Posizione del nastro perpendicolare alla pressa.
Perpendicular position of the conveyor respect the moulding machine.

Tapis posé perpendiculairement à la presse.
Posición de la cinta en perpendicular a la máquina.
Que zur Spritzgussmaschine aufgestelltes Förderband.